

Vertical Glass Door Freezer Specifications

GENERAL

| | | |
|-------------------------------|-----------|---|
| MODEL | VFG 1597N |  |
| CAPACITY IN LITERS | 550 | |
| NUMBER OF SHELVES | 5 | |
| EXTERNAL DIMENSIONS (WxDxH)CM | 71x65x204 | |
| DOOR TYPE (SWING- SLIDING) | 1 swing | |
| GROSS WEIGHT (KGS) | 126 | |

COMPONENT/PERFORMANCE

| | | |
|-----------------------------|--|---|
| INTERNAL CABINET MATERIAL | | high impact resistant plastic |
| INSULATION MATERIAL | | cfc free polyurethane foamed |
| EXTERNAL CABINET MATERIAL | | prepainted steel metal rust proof |
| EXTERNAL CABINET THICKNESS | | Walls 0.5 mm buttom 1 mm |
| SHELVES MATERIAL | | steel wire coated polyethylene food safe |
| COMPRESSOR MANUFACTURER | | Cubigel |
| START UP CAPACITOR | | Present |
| REFRIGERANT GAS | | R290 |
| CONDENSER | | steel fins specially treated with electrophoratic |
| HANDLE | | Built in with door profile |
| VOLTAGE /FRQUENCY | | 220-240V/50-60Hz |
| VOLTAGE RANGE | | 165~240V |
| DOOR FRAME MATERIAL | | Plastic (P.V.C Scratched proof) |
| NUMBER OF DOOR GLASS LAYERS | | Triple glass sheet |
| GLASS MATERIAL | | Three layers |
| GLASS SPECIFICATION | | injected with argon gas between glass layers |
| LOCK | | optional |
| LIGHT SWITCH | | Present |
| WHEELS(NUMBER) | | 2 rear heavy duty wheels (uni-direction) |
| DIGITAL THERMOMETER | | optional |
| LIGHTENING | | 1 internal +1 external canopy |
| ENERGY CONSUMPTION | | 4.6 KW/24H |
| LEVELING FEET | | 2 front |
| THERMOSTAT SETTING RANGE | | -30 °c |

BRANDING

| | | |
|---|--|---------------------|
| SIDE PANEL PRINTING /DIMENSIONS (WxH) cm | | optional /(54x200) |
| TOP PANEL PRINTING /DIMENSIONS (WxH) cm | | optional /(56x31.5) |
| BRAND SHELF PRINTING /DIMENSIONS (WxH) cm | | optional /(45x3.5) |

OTHERS

| | | |
|-----------------------------------|--|-------|
| QTY IN CONTAINER (20' ft / 40'ft) | | 21/51 |
|-----------------------------------|--|-------|