

Cod. AFI4EKOMTN

400

Armadio Refrigerato GN 2/I monoblocco in Acciaio Inox a temperatura normale con 2 porte2 doors Normal Temperature Stainless Steel GN 2/I Refrigerated Cabinet - Armoire Réfrigérée GN 2/I en Acier Inox avec 2 portes -
Edelstahl-Kühlschrank GN 2/I mit Monoblockaggregat, mit 2 Türen

0/+10°C

DIMENSIONI - DIMENSIONS DIMENSIONS - MABE	WxDxH mm	1420x800x2030/2100
DIMENSIONI IMBALLO - PACKAGING DIMENSIONS DIMENSIONS D'EMBALLAGE - MABEVERPACKUNG	WxDxH mm	1460x840x2200
PESO NETTO - NET WEIGHT POIDS NET - NETTOGEWICHT	kg	150
CAPACITA' NETTA - NET CAPACITY CAPACITÉ NET - NUTZINHALT	l	1400
TEMPERATURA D'ESERCIZIO - WORKING TEMPERATURE TEMPÉRATURE DE SERVICE - ARBEITSTEMPERATUR	°C	0 / +10
GAS REFRIGERANTE - GAS GAZ RÉFRIGÉRANT - KÄLTEMITTEL	GAS	R404A/R507
COLLAUDO - TEST DETAILS DETAILS D'ESSAI - PRÜFUNGSERGEBNISSE	°C / RH	+43 / 65%
ASSORBIMENTO ELETTRICO - ABSORBED POWER PUISSANCE ABSORBÉE - ANSCHLUßWERT	W	570
ALIMENTAZIONE - POWER SUPPLY ALIMENTATION - NETZSPANNUNG	V-P-Hz	230-I-50

Dotazione per allestimento interno: 6 Griglie plastificate Rilsan GN 2/I e 12 guide in Acciaio Inox - **Internal standard set-up:** 6 plastic-coated Rilsan grids GN 2/I and 12 Stainless Steel Runners - **Composition Standard:** 6 Clayettes plastifiées Rilsan et 12 glissières en Acier Inox - **Standardausstattung:** 6 rilsanierte Roste GN 2/I und 6 paar Edelstahlschienen



Cod. A4I4EKOMTN

400

Armadio Refrigerato GN 2/I monoblocco in Acciaio Inox a temperatura normale con 4 sportelli4 half doors Normal Temperature Stainless Steel GN 2/I Refrigerated Cabinet - Armoire Réfrigérée GN 2/I en Acier Inox avec 4 portes -
Edelstahl-Kühlschrank GN 2/I mit Monoblockaggregat, mit 4 Halbtüren

0/+10°C

DIMENSIONI - DIMENSIONS DIMENSIONS - MABE	WxDxH mm	1420x800x2030/2100
DIMENSIONI IMBALLO - PACKAGING DIMENSIONS DIMENSIONS D'EMBALLAGE - MABEVERPACKUNG	WxDxH mm	1460x840x2200
PESO NETTO - NET WEIGHT POIDS NET - NETTOGEWICHT	kg	156
CAPACITA' NETTA - NET CAPACITY CAPACITÉ NET - NUTZINHALT	l	1400
TEMPERATURA D'ESERCIZIO - WORKING TEMPERATURE TEMPÉRATURE DE SERVICE - ARBEITSTEMPERATUR	°C	0 / +10
GAS REFRIGERANTE - GAS GAZ RÉFRIGÉRANT - KÄLTEMITTEL	GAS	R404A/R507
COLLAUDO - TEST DETAILS DETAILS D'ESSAI - PRÜFUNGSERGEBNISSE	°C / RH	+43 / 65%
ASSORBIMENTO ELETTRICO - ABSORBED POWER PUISSANCE ABSORBÉE - ANSCHLUßWERT	W	570
ALIMENTAZIONE - POWER SUPPLY ALIMENTATION - NETZSPANNUNG	V-P-Hz	230-I-50

Dotazione per allestimento interno: 8 Griglie plastificate Rilsan GN 2/I e 16 guide in Acciaio Inox - **Internal standard set-up:** 8 plastic-coated Rilsan grids GN 2/I and 16 Stainless Steel Runners - **Composition Standard:** 8 Clayettes plastifiées Rilsan et 16 glissières en Acier Inox - **Standardausstattung:** 8 rilsanierte Roste GN 2/I und 8 paar Edelstahlschienen

