



No.145, 11th Industry Rd. Ta-Li City,
Taichung Hsien 412 Taiwan
Phone:886-4-2491-7585
E-Mail:spar@tcts.seed.net.tw

SP-25MA Mixer

Specifications

● **Motor** <<<<<<
3/4 HP (550W), grease packed ball bearing,
air-cooled, 110/220/1 (50Hz available)

● **Controls** <<<<<<
The following controls are standard on all Spar
Mixers: separate start and emergency stop buttons so
operators can shut down the mixer immediately in an
emergency situation, and thermal overload protection.

● **Cord and Plug** <<<<<<
6 ft. flexible three wire cord and ground prong.

● **Transmission** <<<<<<
Heat-treated, hardened alloy, precision milled gears
operate with planetary action. Gears are packed in a
long-lasting, high pressure grease. Planetary gears
are driven by an oversized cog-wheel, which is in turn
driven by a cogged belt powered by the motor drive
shaft. Cogged belt is a long-lasting, rugged
fibre/rubber composite. This unique design yields
high-torque mixing power while avoiding the high cost
encountered repairing direct-drive transmission
components.

● **Speeds:** <<<<<<

Speed	Agitator rpm	Hub rpm's
Low Speed	108	57
Intermediate Speed	183	105
High Speed	352	202

● **Bowls and Agitators** <<<<<<
Standard equipment includes a 24Qt. (23L) high
quality stainless steel bowl, dough hook, flat beater,
and whip. A sturdy hand lever on the body column
raises and lowers the bowl as well as locking in place
at the top and bottom positions.

● **Attachments** <<<<<<
Standard is the No. 12 hub for powering a standard
size vegetable slicer/cheese shredder and a standard
size meat mincer/grinder.



SP-25MA Mixer

● **Finish** <<<<<<
Top (transmission cover): metallic
bronze epoxy enamel
Bottom: metallic gray epoxy enamel

● **Shipping Information** <<<<<<
N.W. 110kgs
G.W. 140kgs

Carton Size:
Depth x Width x Height
61cm x 67cm x 102cm

Cartons are affixed to an under-
sized skid (pallet), the weight and
diminsions of this skid are not
included above and may vary from
shipment to shipment.

SP-25MA <<<<<<