



T04MP

CAPACITY, DIMENSIONS, WEIGHT	///
Capacity trays	4 TRAYS 600x400 - GN 1/1
Distance between trays (mm)	75
Type of rack holder	GRID
Unit size with handle WxDxH (mm)	750 x 695 x 553
Unit size without handle WxDxH (mm)	750 x 645 x 553
Chamber size WxDxH (mm)	660 x 457 x 340
Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	760 x 760 x 704
Unit weight (kg)	45
Unit weight with packaging (kg)	50
ELECTRICAL DATA	///
Number of engines	2
Frequency (Hz)	50
Power (kW)	6,1
Voltage A	400V 3N~
B	400V 2N~
C	230V ~
D	230V 3~
Current (A) A	13
B	13,6
C	26,7
D	22,6

Power cord/power plug	A
	B
	C
	D
WATER CONNECTION REQUIREMENTS	///
Water inlet	YES
Water drain	-
Minimum water quality standards	5° f
FUNCTIONAL CHARACTERISTICS	///
Supply	ELECTRIC
Certification	-
Control panel	MECHANICAL
Multilingual screen	-
Cooking type	CONVECTION
Bidirectional motors	YES
Two speed regulation	-
Max cooking temperature (°C)	280
Cooking chamber material	AISI 430
Opening door	FROM RIGHT TO LEFT
Easy clean internal glass	-
STANDARD EQUIPMENT	///
Self clean system	-
Core probe	-
VARIANTS AVAIABLES	///
Certification	-
Unit size with handle WxDxH (mm)	-
Unit size without handle WxDxH (mm)	-
Frequency (Hz)	60
Power (kW)	-
Voltage	A -
	B -
	C -
	D -
Current (A)	A -
	B -
	C -
	D -
Power cord / power plug	A -

	B	-
	C	-
	D	-
Packaging		-
Packaging size WxDxH (mm)		-
ACCESSORIES		///
Self clean system		-
Stainless steel tray rack holder		-
Stainless steel grid rack holder		"4 TRAYS GN 1/1 75mm"
Oven stand		T8
		T8S
		T8SL
Wheels kit for stand		R60B
Condensation hood		CK01
Water condensation hood		-
Proofer		CA8008M0
		CA8008MH
		CA8008DH
Overlapping kit for 2 ovens		SK5
Blast chiller		KDA03
		KDA05
		ASP05
Overlapping kit for blast chillere + 1 ovens		-
Smoker		-
Core probe		-
Core probe for vacuum		-
Water softner cover		WS10
Water softner 6800L		WS11
Water softner 12000L		WS12
Water pressure adaptor		WPA
Manual shower kit		-
"Detergent 750ML (for Self clean system or Manual shower kit)"		-
"Detergent 6KG (only with self clean system)"		-
"Detergent 10KG (only with self clean system)"		-
		-

FEATURES

◆ Standard | ◇ Optional | - Not available

MANUAL COOKING		
Convection cooking	30°C - 285°C	◆
Mixed humidity and convection cooking	90°C - 230°C	◆
Humidity		-
Grill		-
AUTOMATIC COOKING		
Program: possibility to memorize program		-
V-EVOLUTION CONTROL WITH 6 SPEED PROGRAMS		-
Cooking cycles for each program		-
Automatic pre-heating setting		-
AIR DISTRIBUTION IN THE COOKING CHAMBER		
V-BI.DIRETIONAL REVERSING FAN		-
V-POWERFULL ENGINE		-
Number of speed regulation		-
OVERLAP SYSTEM		
V- OVERLAP CONNECTION with ovens		◇
V- OVERLAP CONNECTION with Venix's Proofing		◇
V- OVERLAP CONNECTION with Venix's Stand		◇
OTHER FUNCTIONS		
Infinity time		◆
Temperature parameter unit F° or C°		◆
V - LIGHTS	Halogen	◆
USB		-
TECHNICAL DETAILS		
Internal glass easy clean system		◆
Thermal insulation structure (energetic efficiency)		◆
Humidity regulation	Manual	◆